

type	size	max. bending loads	max. slip load		max. tensile load	
			1 cs-g-t.	2 cs-g-t.	1 cs-g-t.	2 cs-g-t.
		(KNm)	(KN)	(KN)	(KN)	(KN)
L 10	7	0,90	7,0	-	6,0	-
L 10	8	1,0	7,0	-	7,0	-
L 14	7	0,3	-	-	7,0	-
L 14	8	0,6	-	-	8,0	-
L 15	7	0,90	-	-	7,0	-
L 15	8	0,75	-	-	8,0	-
L 19 ⁽¹⁾	7	-	7,0	-	7,0	-
L 19 ⁽¹⁾	8	-	8,0	-	8,0	-
L 20	7	0,75	-	-	6,0	-
L 20	8	0,90	-	-	7,0	-
L 21	7	0,40	7,0	-	6,0	-
L 21	8	0,75	8,0	-	8,0	-
L 25	7	1,0	-	14,0	7,0	-
L 25	8	1,0	-	16,0	8,0	-
L 26	7	0,9	7,0	-	7,0	-
L 26	8	1,0	7,0	-	8,0	-
L 45	7	0,90	7,0	-	-	-
L 45	8	0,90	8,0	-	-	-
L 61	7	0,75	-	-	7,0	-
L 61	8	0,90	-	-	8,0	-
L 62	7	0,75	-	-	-	14,0
L 62	8	0,90	-	-	-	14,0
L 68	7	0,90	-	-	-	14,0
L 68	8	0,90	-	-	-	14,0
L 114	7	0,90	7,0	-	-	-
L 114	8	0,75	7,0	-	-	-
L 150	8	1,2	-	-	-	11,0
L 152	7	1,0	-	-	7,0	-
L 152	8	1,2	-	-	8,0	-
L 164	8	1,2	-	-	-	15,0
LM 50 ⁽¹⁾	7	-	7,0	-	-	-
LM 50 ⁽¹⁾	8	-	8,0	-	-	-
LF 50 ⁽¹⁾	7	-	-	-	7,0	-
LF 50 ⁽¹⁾	8	-	-	-	8,0	-
LM 58 ⁽²⁾	7/8	-	-	-	10,0	-

¹⁾ The fittings named LF 50, LM 50, LM 58 and L 19 are not constructed to absorb bending load, bending moments are not allowed

²⁾ The stated tensile load refers to the swivel eye, tensile direction 45 degrees to flange-base

Eschborn, 2002-02-19
 Mechanical products

